


PRODUCT TECHNICAL DATASHEET

BI/004

Brushless
Digital Encoder




CODE	DESCRIPTION	PCS/PALLET
BI/004	Barrier BRUSHLESS 36V DC for 3 or 4 metre booms, with control unit and on board native encoder, complete with a fastening base with tie rods and screws and boom fastening angles.	8

PRODUCT TECHNICAL SPECIFICATIONS	
Barriers	Up to 4mt long
Power line supply	230V AC - 50 Hz
Motor power supply	36V DC
Electrical absorption	0-15A
Power rating	220W
Frequency of use	Continue
Torque	0 - 200 N m
Operating temperature	- 20 + 55 C°
Protection level	IP54
Reductor Type	Irreversible
Opening time	1,5÷6 sec (up to 3 m) - 3÷6 sec (up to 4 m)
Onboard control unit	CTRL Digital Controller 36V DC
Encoder	Digital native encoder + magnetic digital SENSORED, 4096 PPR
Accessories power supply	24V DC
Colour	Cabinet: painted RAL9006 arabesque grey - Head: black arabesque silver painted - Boom support: plastic RAL9005 - Boom: painted RAL9010 matt
Release system	STANDARD Key cylinder - Optional European Cylinder (Cod. RL670)
Batteries recovery	Available (optional)
BUS synchronization Master/Slave	Yes


Operating cycles per day (opening/closing - 24 hours no stop)	5000 cycles
Maximum dimension product in mm (L x W x H)	280 x 210 x 1203
Product weight packed (Kg)	46,2
Number items per pallet/box	8

PRODUCT DIMENSIONS AND PREPARING FOR INSTALLATION




DIMENSIONS


PRODUCT ACCESSORIES




BAFS/01
Fixed support for bars.



BAFS/02
Fixing support, adjustable.




BAFS/03
Fixing support with bolt predisposition for bars.




BAFS/04
Fixing support adjustable, with bolt predisposition for bars.



BAFS/05
Adjustable fixed support with vandal-proof magnetic suction cup complete with B72/DGS demagnetizer card.




BAMS/01
Mobile support for bars.




BAMS/01/EXT
Extension 20cm for mobile support BAMS/01.




BA/68/3
White painted aluminum rod, 3 meters long, with LED cover profile and impact resisting rubber profile.




BA/68/4
White painted aluminum rod, 4 meters long, with LED cover profile and impact resisting rubber profile.




SND/BA/68/DW
Articulated joint 90° with lower tie rod for boom arms BA/68.



SND/BA/68/UP
Articulated joint 90° with upper tie rod for boom arms BA/68.



SND/BA/68/UP/RD
Articulated joint 90° with upper tie rod (lowered version) for boom arms BA/68.



BARK/02
Barrier skirting in aluminum, with stainless steel screws mounted on bronze bushings. Single module of length 2 meters.




ACS/BA/60
Break-away system for barrier, compatible only with BA/60/3 boom arm.



ACS/BA/68
Break-away system for barrier, compatible with BA/68/3 and BA/68/4 boom arm.



KT247
Support for rectangular boom for BI/004 up to 4 m and max. 3.6 kg.



BI/BAT/KIT
Kit for emergency batteries charger for brushless digital controller CTRL 36V DC with plug-in card, with 2 recovery batteries 12V DC, 4.5 Ah. Kit for BIONIK barrier.



BI/BCHP
Plug-in card, batteries charger, for brushless digital controller CTRL 36V DC, without recovery batteries, for BIONIK barrier.



BT12V45
Battery 12V 4.5 Ah (1 pc).




B71/PBX36/BOX
Hybrid inverter, "Network Assisted" version, for powering the automation. Also provides a battery-charger function thanks to the connection to the solar panels or mains supply for powering the 36V DC brushless digital controllers with a mains voltage of 230V AC.




B71/PBX36/BOX/115
Hybrid inverter, "Network Assisted" version, for powering the automation. Also provides a battery-charger function thanks to the connection to the solar panels or mains supply for powering the 36V DC brushless digital controllers with a mains voltage of 115V AC.



B71/PBX/BOX
Hybrid inverter, "Full Solar" version, for powering the automation. Also provides a battery-charger function thanks to the connection to the solar panels for powering the brushless digital controllers.



KT231
Fixing plate for code BAFS/01, BAFS/02, BAFS/03, BAFS/04, BAFS/05.



KT240
Fixing plate with stay bolts and screws for BI/004.



B73/EXP
Signal status board, 2 output for CTRL - CTRL/P




B73/LTM
RGB boom light and traffic light control device for CTRL



B74/BCONNECT vers. HW2
Module Wi-Fi B-CONNECT - Remote management and programming system in IP web browser mode via Wi-Fi hot spot P2P connection for Brushless control units (B70/2ML - EDGE1 - CTRL - B70/1DC - B70/1DCHP - B70/1T - B70/1THP - F70/IPU36).




SP/48/G14
Spring diameter 48 mm only for BI/004 with boom less than 2.2 m.



SP/48/01
Spring diameter 48 mm for barriers.



SP/61/01
Spring diameter 61 mm for barriers.



SP/72/01
Spring diameter 72 mm for barriers.



DLD1/24
Loop detector for 1 loop, 2 output, 24V AC/DC.



DLD2/24
Loop detector for 2 loop, 2 output + output alarm, 24V AC/DC.



RL670
European cylinder key for release system series SMARTY - BIONIK.



KT239
Kit DIN rail with magnetic support.



KT242
Cable passage kit with magnetic support for barriers.



ALED/4C
4-metre LED strip with connection cable for barrier boom (red colour).



ALED/4C/RGB
4-metre multicoloured RGB LED (red, green + other colours) strip with connection cable for barrier boom.



BI/BLED/4/RGB
Multicoloured RGB LED strip (red, green + other colours) with connection cable for BI/004 barrier header.



R99/BASB20
Pack of 20 stickers for barrier.



R99/BASB40
Pack of 40 stickers for barrier.